





Standard version



Optionals version



HS 6000 E			
Motore Engine		Generatore Generator	
Potenza Power (HP/3600 r.p.m.)	9,6	Frequenza Frequency	50 Hz.
Avviamento Start system	manuale elettrico recoil electric	Tensione Voltage	230 Volt
Cilindrata Displacement	418 cc	Potenza uso continuo Continuous duty power	6 kVA
Tipo carburante Fuel	Diesel	Potenza max Max. power	6,5 kVA
Capacità serbatoio Tank capacity	5,5 lt	Peso Weight	100 Kg
Servizio continuo orario Continuous duty running time	5 h	Dimensioni Dimensions	L = 860 P = 740 H = 800

Generatore diesel

Gruppo elettrogeno monofase con motore diesel, flangiato ad un alternatore a 2 poli monofase. Avviamento con autoavvolgente ed elettrico a batteria. Quadro di comando con 2 prese monofase CEE 16A e 2 protettori termici. Optional: pannello prese con 1 presa monofase CEE 32A, 1 presa monofase CEE 16A e 2 protettori termici.

Diesel engine generator

Single phase generating set with diesel engine coupled to single phase 2-pole alternator. Recoil or electric starter with battery. Control panel with 2 single phase CEE plugs 16A and 2 termic protectors. Optional: control panel with 1 single phase CEE plug 32A, 1 single phase CEE plug 16A and 2 termic protectors.