



**TECHNICAL DATA:**

MODEL		RID 150 B-SERIES	RID 150 B-SERIES S	RID 200 B-SERIES	RID 200 B-SERIES S
Version		open skid	silent	open skid	silent
<b>Order number Generator</b>		<b>713744</b>	<b>713745</b>	<b>713708</b>	<b>713710</b>
Order number Generator with ATS		-	-	-	-
Order number Generator external ATS		728316	728316	728317	728317
Nom. output P.R.P. (cos = 0,8)	kVA/kW	150 / 120		200 / 160	
Nom. total current (cos = 0,8)	A	217		289	
Voltage	V	230 / 400		230 / 400	
Frequency	Hz	50		50	
Dimensions (L x W x H)	mm	2600x1200x1940	3350x1430x2114	2600x1200x1940	3350x1430x2114
Weight	kg	1820	2190	2028	2500
Noise level	dB(A)	83	69	85	69
Fuel tank capacity	l	750		1000	
<b>Engine</b>	<b>Doosan</b>	<b>DP086TA</b>		<b>P086TI</b>	
Speed range	rpm	1500		1500	
Speed governor		electrical		electrical	
Fuel		diesel		diesel	
Cooling system		Water + air		Water + air	
Displacement	l	8,07		8,07	
Engine output	kW	137		177	
Starter	V	24		24	
Oil type (recommended)		RID 10W40		RID 10W40	
Engine oil volume	l	15,5		15,5	
Fuel consumption load 100/75%	l/h	33,7 / 25,5		35,4 / 26,5	
<b>Generator</b>		<b>synchronous</b>		<b>synchronous</b>	
Isolation type		H		H	
Protection class		IP 23		IP 23	

OPTIONS (description - page 44)	ORDER NUMBER			
Coolant heater	715112	715112	715129	715129
Fuel filter / water separator	754035	754035	754053	754053
External fuel tank 720 / 1000 L	718000 / 718010	718000 / 718010	718000 / 718010	718000 / 718010
Automatic fuel refilling system	on request	on request	on request	on request
Battery charger	733339	733339	733339	733339
RID LTE Modem	on request	on request	on request	on request
RID overvoltage protection	734033	734033	734033	734033