



MADE IN GERMANY

**10 - 15 KVA ENGINE BRIGGS & STRATTON**~230  
VOLT  
25 L~400  
VOLT**TECHNICAL DATA:**

TYPE		RV 10000 E	RV 10001 E	RV 12001 E	RV 13000 E	RV 15000 E
<b>Order number</b>		<b>717025</b>	<b>717023</b>	<b>717027</b>	<b>717026</b>	<b>717028</b>
Generator type		synchronous	synchronous	synchronous	synchronous	synchronous
Nom. output 3~ (cos $\Phi=0,8$ )	kVA	10,0	-	-	13,0	15,0
Nom. output 1~	kVA	5,8	10,0	12,0	7,4	7,4
Voltage (1~) / (3~)	V	230 / 400	230 / -	230 / -	230 / 400	230 / 400
Nom. current (1~) / (3~)	A	25,1 / 14,4	43,5 / -	52,0 / -	32,0 / 19,5	32,0 / 23,1
Frequency	Hz	50	50	50	50	50
Protection Class		IP23	IP23	IP23	IP23	IP23
<b>Engine type</b>		<b>Vanguard 385447</b>	<b>Vanguard 385447</b>	<b>Vanguard 385447</b>	<b>Vanguard 385447</b>	<b>Vanguard 386447</b>
Cylinder		2	2	2	2	2
Rotational-speed range	rpm	3000	3000	3000	3000	3000
Type of fuel		gasoline 92 / 95	gasoline 92 / 95	gasoline 92 / 95	gasoline 92 / 95	gasoline 92 / 95
Oil		SAE 15W-40	SAE 15W-40	SAE 15W-40	SAE 15W-40	SAE 15W-40
Oil volume in engine	l	1,7	1,7	1,7	1,7	1,7
Engine output	kW	13,0	13,0	13,0	13,0	13,5
Cooling		air	air	air	air	air
Tank capacity	l	25	25	25	25	25
Hand starter (H) / electr. starter (E)		H / E	H / E	H / E	H / E	H / E
Fuel consumption load 100%	l/h	6,7	6,7	6,7	6,7	6,7
Weight	kg	115	125	130	130	133
Dimensions (L x W x H)	mm	848 x 649 x 620	848 x 649 x 620	848 x 649 x 620	848 x 649 x 620	848 x 649 x 620
Noise level	dB(A)	72	72	72	72	72

OPTIONS	DESCRIPTION	ORDER NUMBER
Exhaust hose	Ø 50 mm, length 1,5 m	715052
Exhaust hose	Ø 50 mm, length 2,5 m	715051
Engine adapter for exhaust hose	for engines Briggs & Stratton VANGUARD	716010
Chassis with wheels and handles	for all types on tubular frames	713203
Earthing set	earthing pike (0,45 m length), earthing cable 10 mm <sup>2</sup>	736110
Spare parts	for all products of equipment	on request